



|  |                  |
|--|------------------|
| <b>Bestellbezeichnung:</b><br>ordering code:   | <b>Aluminium</b> |
| • Flansch incl. metrischem Schraubensatz u. O-Ring<br>flange including metric bolts and o-ring | WDA-...K         |

| maximaler Betriebsdruck<br>maximum recommended working pressure | Lochkreis<br>hole-figuration | Typ<br>type               | Abmessungen<br>dimensions |      |                |                |      | Schrauben<br>bolts | O-Ring<br>o-ring | Gewicht<br>(nur Flansch)<br>weight<br>(flange only) |
|---|------------------------------|---------------------------|---------------------------|------|----------------|----------------|------|--------------------|------------------|---|
|   |                              |                           | A                         | B    | S <sub>1</sub> | S <sub>2</sub> | L    |                    |                  |   |
| 180   | 26,0                         | WDA 05/38                 | G 3/8"                    | 10,0 | 18,0           | 31             | 5,3  | 3 x M5 x 35        | 14 x 1,78        | 0,06  |
| 180   | 26,0                         | WDA 05/12                 | G 1/2"                    | 10,0 | 18,0           | 31             | 5,3  | 3 x M5 x 35        | 14 x 1,78        | 0,05  |
| 180   | 30,0                         | WDA 1/38                  | G 3/8"                    | 12,5 | 18,0           | 30             | 6,5  | 3 x M6 x 35        | 15,88 x 2,62     | 0,08  |
| 180   | 30,0                         | WDA 1/12                  | G 1/2"                    | 12,5 | 18,0           | 30             | 6,5  | 3 x M6 x 35        | 15,88 x 2,62     | 0,08  |
| 180   | 40,0                         | WDA 2/12                  | G 1/2"                    | 18,5 | 20,0           | 40             | 8,5  | 3 x M8 x 45        | 22,22 x 2,62     | 0,15  |
| 180   | 40,0                         | WDA 2/34                  | G 3/4"                    | 18,5 | 20,0           | 40             | 8,5  | 3 x M8 x 45        | 22,22 x 2,62     | 0,16  |
| 180   | 51,0 - 56,0                  | WDA 3/34                  | G 3/4"                    | 25,0 | 26,0           | 46             | 10,5 | 3 x M10 x 60       | 29,75 x 3,53     | 0,32  |
| 180   | 51,0 - 56,0                  | WDA 3/100                 | G 1"                      | 25,0 | 26,0           | 46             | 10,5 | 3 x M10 x 60       | 29,75 x 3,53     | 0,33  |
| 120   | 62,0                         | WDA 3,5/114 <sup>*1</sup> | G 1 1/4"                  | 32,0 | 33,5           | 57             | 13,0 | 2 x M12 x 35       | 35,80 x 3,53     | 0,39  |
| 120   | 72,5                         | WDA 4/112 <sup>*1</sup>   | G 1 1/2"                  | 40,0 | 38,0           | 64             | 13,0 | 2 x M12 x 35       | 44,04 x 3,53     | 0,49  |

\*1 Ausführung: 2 Lochflansch / Type: 2-hole flange