



<b>Bestellbezeichnung:</b> ordering code:	<b>S355J2<sup>*1</sup></b> C22	<b>1.4404<sup>*1</sup></b> 316L
• nur Außengewindeflansch adaptor only	SFCE-...J	SFCE-X-...J
• incl. Flanschhälften, metrischem Schraubensatz und O-Ring including split flanges, metric bolts and o-ring	SFCE-...JM	SFCE-X-...J...MX
• incl. Flanschhälften, UNC-Schraubensatz und O-Ring including split flanges, UNC bolts and o-ring	SFCE-...JU	SFCE-X-...J...UX

maximaler Betriebsdruck maximum recommended working pressure	S.A.E. Baugröße nominal flange size	Typ type	Abmessungen dimensions										Schrauben bolts		Gewicht weight		
			A	A1	B	C	D	E	F	G	SW	L	M	kg			
kg/cm <sup>2</sup>	inch																
<b>Schraube Festigkeitskl.</b> 10.9	<b>Standarddruckreihe / Standard pressure</b>													<i>metr.</i>	<i>unc.</i>		
350	1/2"	SFCE 3001-J 7/8	7/8" -14UN	30,2	12,3	38,1	54	17,5	46	48	20	8,50	M 8x25	5/16 x 1 1/4	-		
350	3/4"	SFCE 3002-J 1 1/16	1 1/16" -12UN	38,1	15,5	47,6	65	22,3	52	55	30	10,50	M 10x30	3/8 x 1 1/4	-		
320	1"	SFCE 3003-J 1 1/16	1 1/16" -12UN	44,5	15,5	52,4	70	26,2	59	55	36	10,50	M 10x30	3/8 x 1 1/4	-		
280	1 1/4"	SFCE 3004-J 1 5/16	1 5/16" -12UN	50,8	21,5	58,7	79	30,2	73	58	42	*2	*3	7/16 x 1 1/2	-		
280	1 1/4"	SFCE 3004-J 1 5/8	1 5/8" -12UN	50,8	27,5	58,7	79	30,2	73	58	42	*2	*3	7/16 x 1 1/2	-		
210	1 1/2"	SFCE 3005-J 1 7/8	1 7/8" -12UN	60,3	33,0	69,9	94	35,7	83	62	42	13,30	M 12x35	1/2 x 1 1/2	-		
<b>Schraube Festigkeitskl.</b> 10.9	<b>Hochdruckreihe / High pressure</b>													<i>metr.</i>	<i>unc.</i>		
350	1/2"	SFCE 6001-J 1 1/16	1 1/16" -12UN	31,8	15,5	40,5	56	18,2	48	50	20	8,50	M 8x30	5/16 x 1 1/4	-		
350	1/2"	SFCE 6001-J 7/8	7/8" -14UN	31,8	12,3	40,5	56	18,2	48	50	20	8,50	M 8x30	5/16 x 1 1/4	-		
350	1/2"	SFCE 6001-J 3/4	3/4" -16UN	31,8	9,9	40,5	56	18,2	48	50	20	8,50	M 8x30	5/16 x 1 1/4	-		
350	3/4"	SFCE 6002-J 1 1/16	1 1/16" -12UN	41,3	15,5	50,8	71	23,8	60	64	30	10,50	M 10x35	3/8 x 1 1/2	-		
350	1"	SFCE 6003-J 1 1/16	1 1/16" -12UN	47,6	15,5	57,2	81	27,8	70	72	36	*4	M 12x45	7/16 x 1 1/2	-		
350	1"	SFCE 6003-J 1 5/16	1 5/16" -12UN	47,6	21,5	57,2	81	27,8	70	72	36	*4	M 12x45	7/16 x 1 1/2	-		
350	1 1/4"	SFCE 6004-J 1 5/16	1 5/16" -12UN	54,0	21,5	66,6	95	31,8	78	81	41	14,60	M 14x50	-	-		
350	1 1/4"	SFCE 6004-J 1 5/16-M12	1 5/16" -12UN	54,0	21,5	66,6	95	31,8	78	81	41	13,30	M 12x45	1/2 x 1 3/4	-		
275	1 1/4"	SFCE 6004-J 1 5/8	1 5/8" -12UN	54,0	27,5	66,6	95	31,8	78	81	41	14,60	M 14x50	-	-		
275	1 1/4"	SFCE 6004-J 1 5/8-M12	1 5/8" -12UN	54,0	27,5	66,6	95	31,8	78	81	41	13,30	M 12x45	1/2 x 1 3/4	-		
275	1 1/2"	SFCE 6005-J 1 5/8	1 5/8" -12UN	63,5	27,5	79,3	113	36,5	95	86	41	16,80	M 16x55	5/8 x 2	-		
210	1 1/2"	SFCE 6005-J 1 7/8	1 7/8" -12UN	63,5	33,0	79,3	113	36,5	95	86	42	16,80	M 16x55	5/8 x 2	-		

Oberfläche: CR-6: auslaufend/Neu: CR-6 frei / surface: CR-6: phase-out/New: CR-6 free  
\*1 oder vergleichbare Güte / or comparable material

\*2 wahlweise 10,50, 12,00 oder 12,75 / choice of 10.50, 12.00 or 12.75

\*3 wahlweise M 10x30 oder M 12x35 / choice of M 10x30 or M 12x35

\*4 wahlweise 12,0 oder 13,0 / choice of 12.0 or 13.0