



<b>Bestellbezeichnung:</b> ordering code:	<b>S355J2<sup>*1</sup></b>	<b>1.4404<sup>*1</sup></b> 316L
• nur Flansch flange only	AFC-...G1/4"	AFC-X-...G1/4"
• incl. metrischem Schraubensatz und O-Ring including metric bolts and o-ring	AFC-...G1/4"M	AFC-X-...G1/4"MX
• incl. UNC-Schraubensatz und O-Ring including UNC bolts and o-ring	AFC-...G1/4"U	AFC-X-...G1/4"UX

maximaler Betriebsdruck maximum recommended working pressure	S.A.E. Baugröße nominal flange size	Typ type	Abmessungen dimensions						Schrauben bolts		Gewicht weight	
			C	D	E	F	H	L	M	kg		
kg/cm <sup>2</sup>	inch											
Schraube Festigkeitskl. 10.9	Standarddruckreihe / Standard pressure									metr.	unc.	
350	1/2"	AFC 080 G1/4"	38,1	56	17,5	48	16	9,0	M 8x30	5/16 x 1 1/4	0,20	
350	3/4"	AFC 100 G1/4"	47,6	65	22,3	50	16	11,0	M 10x35	3/8 x 1 1/2	0,30	
320	1"	AFC 102 G1/4"	52,4	70	26,2	60	19	11,0	M 10x35	3/8 x 1 1/2	0,37	
280	1 1/4"	AFC 104 G1/4"	58,7	79	30,2	68	18	11,5	M 10x40	7/16 x 1 1/2	0,54	
210	1 1/2"	AFC 106 G1/4"	69,9	93	35,7	78	20	13,5	M 12x45	1/2 x 1 3/4	0,90	
210	2"	AFC 108 G1/4"	77,8	102	42,9	90	20	13,5	M 12x45	1/2 x 1 3/4	1,00	
175	2 1/2"	AFC 110 G1/4"	88,9	114	50,8	105	20	13,5	M 12x45	1/2 x 1 3/4	1,35	
160	3"	AFC 112 G1/4"	106,4	134	61,9	124	24	17,5	M 16x50	5/8 x 2	2,35	
35	3 1/2"	AFC 114 G1/4"	120,7	152	69,9	136	22	17,5	M 16x50	5/8 x 2	2,90	
35	4"	AFC 116 G1/4"	130,2	162	77,8	146	25	17,5	M 16x50	5/8 x 2	3,90	
35	5"	AFC 118 G1/4"	152,4	190	92,1	170	28	17,5	M 16x55	5/8 x 2	4,00	
Schraube Festigkeitskl. 10.9	Hochdruckreihe / High pressure									metr.	unc.	
420	1/2"	AFC 401 G1/4"	40,5	56	18,2	48	16	9,0	M 8x30	5/16 x 1 1/4	0,20	
420	3/4"	AFC 402 G1/4"	50,8	71	23,8	60	19	11,0	M 10x35	3/8 x 1 1/2	0,48	
420	1"	AFC 403 G1/4"	57,2	81	27,8	70	24	13,0	M 12x45	7/16 x 1 1/2	0,77	
420	1 1/4"	AFC 404 G1/4"	66,6	95	31,8	78	27	15,0 <sup>*2</sup>	M 14x50	1/2 x 1 3/4	0,85	
420	1 1/2"	AFC 405 G1/4"	79,3	112	36,5	94	30	17,0	M 16x50	5/8 x 2	1,80	
420	2"	AFC 406 G1/4"	96,8	134	44,5	114	28	21,0	M 20x65	3/4 x 2 1/2	2,00	
420	2 1/2"	AFC 407 G1/4"	123,8	180	58,8	150	45	26,0	M 24x80	–	5,30	

\*1 oder vergleichbare Güte / or comparable material

\*2 L=13,5 für UNC-Schrauben / L=13.5 with UNC-bolts