



<b>Bestellbezeichnung:</b> ordering code:	<b>S355J2<sup>*1</sup></b>	<b>1.4404<sup>*1</sup></b>
• nur Vollflansch only flange	RRF-...	RRF-X-...

maximaler Betriebsdruck maximum recommended working pressure	S.A.E. Baugröße nominal flange size	Typ type	Abmessungen dimensions								Schrauben bolts		Gewicht weight	
			A	B	C	D	E	F	G	L	Einzel single	Kupplung coupling		
kg/cm <sup>2</sup>	inch										metr.		kg	
<b>Standarddruckreihe / Standard pressure</b>														
350	1/2"	RRF-3001	30,5	26,5	38,1	54	17,5	46	20	9				
350	3/4"	RRF-3002	40,5	36,5	47,6	65	22,2	52,3	20	11				
350	1"	RRF-3003	44,5	39,5	52,4	70	26,2	58,7	20	11				
280	1 1/4"	RRF-3004	51,5	46,5	58,7	79,4	30,2	73,2	20	11				
280	1 1/2"	RRF-3005	61,5	56,5	69,9	94	35,7	82,6	25	13,5				
280	2"	RRF-3006	71,5	66,5	77,8	102,1 *2	42,9	96,8	30	13,5				
210	2 1/2"	RRF-3007	85,5	80,5	88,9	114,3	50,8	108,7	40	13,5				
210	3"	RRF-3008	103,5	97,5	106,4	135	61,9	131,1	50	17,5				
<b>Hochdruckreihe / High pressure</b>														
420	1/2"	RRF-6001	30,5	26,5	40,5	56	18,2	47,8	22	9				
420	3/4"	RRF-6002	40,5	36,5	50,8	71	23,8	60,5	23	11				
420	1"	RRF-6003	44,5	39,5	57,2	81	27,8	69,9	25	13,5				
420	1 1/4"	RRF-6004	51,5	46,5	66,7	95	31,8	77,7	30	15				
420	1 1/4"	RRF-6044	51,5	46,5	66,7	95	31,8	77,7	30	13,5				
420	1 1/2"	RRF-6005	61,5	56,5	79,4	112,8	36,5	95,3	33	17,5				
420	2"	RRF-6006	71,5	66,5	96,8	133	44,5	114,3	38	21				

\*1 oder vergleichbare Güte / or comparable material  
Oberfläche : CR-6 frei / surface CR-6 free

\*2 Maß D bei 1.4404: 112,8 mm