



| | | |
|--|----------------------------|------------------------------------|
| Bestellbezeichnung: ordering code: | S355J2^{*1} | 1.4404^{*1} 316L |
| • nur Block block only | L-GD-... | L-GD-X-... |

| maximaler Betriebsdruck maximum recommended working pressure | S.A.E. Baugröße nominal flange size | Typ type | Abmessungen dimensions | | | | | | | | | | | Gewicht weight | |
|---|--|---|---------------------------|-------|-----|------|------|-----|-----|------|------|------|----|-------------------|----|
| | | | B | C | D | E1 | E2 | F | G | L | M | S1 | S2 | | kg |
| kg/cm ² | inch | | | | | | | | | | | | | | |
| Schraube Festigkeitskl. 10.9 | | Standarddruckreihe / Standard pressure | | | | | | | | | | | | | |
| 350 | 1/2" | L-GD 301 | 13 | 38,1 | 55 | 17,5 | 17,5 | 55 | 50 | 9,0 | M 8 | 25,0 | 35 | 1,0 | |
| 350 | 3/4" | L-GD 302 | 19 | 47,6 | 65 | 22,3 | 22,3 | 60 | 60 | 11,0 | M 10 | 30,0 | 40 | 1,2 | |
| 320 | 1" | L-GD 303 | 24 | 52,4 | 72 | 26,2 | 26,2 | 65 | 65 | 11,0 | M 10 | 33,0 | 40 | 1,9 | |
| 280 | 1 1/4" | L-GD 304 | 32 | 58,7 | 82 | 30,2 | 30,2 | 82 | 80 | 11,0 | M 10 | 39,0 | 38 | 3,5 | |
| 210 | 1 1/2" | L-GD 305 | 38 | 69,9 | 98 | 35,7 | 35,7 | 92 | 92 | 13,5 | M 12 | 51,0 | 59 | 5,0 | |
| 210 | 2" | L-GD 306 | 46 | 77,8 | 102 | 42,9 | 42,9 | 85 | 87 | 13,5 | M 12 | 51,0 | 48 | 7,9 | |
| 175 | 2 1/2" | L-GD 307 | 62 | 88,9 | 115 | 50,8 | 50,8 | 110 | 120 | 13,5 | M 12 | 60,0 | 65 | 8,6 | |
| 160 | 3" | L-GD 308 | 73 | 106,4 | 135 | 61,9 | 61,9 | 150 | 135 | 17,5 | M 16 | 67,5 | 90 | 10,5 | |
| 35 | 3 1/2" | L-GD 309 | 89 | 120,7 | 150 | 69,9 | 69,9 | 145 | 145 | 17,5 | M 16 | 72,5 | 75 | - | |
| Schraube Festigkeitskl. 10.9 | | Hochdruckreihe / High pressure | | | | | | | | | | | | | |
| 420 | 1/2" | L-GD 601 | 13 | 40,5 | 60 | 18,2 | 18,2 | 60 | 50 | 9,0 | M 8 | 25,0 | 40 | 1,0 | |
| 420 | 3/4" | L-GD 602 | 19 | 50,8 | 72 | 23,8 | 23,8 | 60 | 55 | 11,0 | M 10 | 32,0 | 36 | 1,4 | |
| 420 | 1" | L-GD 603 | 23 | 57,2 | 82 | 27,8 | 27,8 | 68 | 64 | 14,0 | M 12 | 37,0 | 40 | 2,3 | |
| 420 | 1 1/4" | L-GD 604 | 30 | 66,6 | 96 | 31,8 | 31,8 | 76 | 72 | 16,0 | M 14 | 41,0 | 46 | 3,3 | |
| 420 | 1 1/2" | L-GD 605 | 38 | 79,3 | 114 | 36,5 | 36,5 | 86 | 89 | 18,0 | M 16 | 50,0 | 52 | 5,4 | |
| 420 | 2" | L-GD 606 | 50 | 96,8 | 133 | 44,5 | 44,5 | 107 | 107 | 21,0 | M 20 | 64,0 | 70 | 9,0 | |
| 420 | 2 1/2" | L-GD 607 | 62 | 123,8 | 180 | 58,8 | 58,8 | 160 | 155 | 26,0 | M 24 | 77,5 | 90 | 14,6 | |

*1 oder vergleichbare Güte / or comparable material