



Bestellbezeichnung: <i>ordering code:</i>	S355J2 *1	1.4404 *1
• Bond / O-Ring Verbinder <i>Bond - o-ring connector</i>	RRF-O-RING-...	RRF-O-RING-X-..

S.A.E. Baugröße <i>nominal flange size</i>	Typ <i>type</i>				Gewicht <i>weight</i>
		A	B	L	kg
<i>inch</i>					
1/2"	RRF-O-RING-012	30	14	7	0,03
3/4"	RRF-O-RING-034	40	20	7	0,05
1"	RRF-O-RING-100	45	24	7	0,06
1 1/4"	RRF-O-RING-114	50	30	7	0,06
1 1/2"	RRF-O-RING-112	60	39	7	0,08
2"	RRF-O-RING-200	70	49	7	0,09
2 1/2"	RRF-O-RING-212	84	60	7	0,13
3"	RRF-O-RING-300	102	72	7	0,20

*1 oder vergleichbare Güte / *or comparable material*, Oberfläche: CR-6 frei / *surface CR-6 free*

Der angeführte maximale Betriebsdruck ist bezogen auf den Flansch! Der tatsächliche Betriebsdruck wird bestimmt durch das Rohr (Wandstärke) sowie die Güte des Rohres!
The maximum recommended working pressure is based on the flange. The working pressure of the system is determined by the tube (thickness) and by the steel quality of the tube!